



BH T2 Copper Cable Lug

BH T2 copper cable lug has good appearance specifications, good electrical conductivity and safety.

Product use:

Suitable for the connection of copper conductors of electrical cable-type wires with electrical equipment with a nominal cross-section of 2.5-400 mm².

Product features:

Long-term working temperature -55°C-150°C, tin plated on the surface.

Product material: T2 copper tube
Surface treatment: Tin plated

Standard:

Complied with IEC61238-1-3:2018



產品	T2 COPPER CABLE LUG T2銅線耳						
吋吋規格	公制(Metric)						
型號	Dimension (mm)					Cable Size (mm ²)	內盒/外盒
	D2Ø	L	L1	dØ	W		
BH2.5-5	5.2	21.6	9.3	2.95	8.4	2.5	2500 / 30000
BH4-5	5.2	22.3	9.2	3.85	8.3	4	2000 / 24000
BH6-6	6.4	23	9	4.1	9.1	6	1000 / 12000
BH10-8	8.4	25	9.5	5.1	9.4	10	1000 / 12000
BH16-8	8.4	30.7	12.2	6.4	11.8	16	500 / 6000
BH25-10	10.5	34	13.3	7.4	13.2	25	300 / 3600
BH35-10	10.5	38	14.5	8.5	15.5	35	200 / 2400
BH50-10	10.5	42.5	16.5	9.6	17.6	50	100 / 1200
BH70-12	13	50	19	11.9	21.2	70	100 / 1200
BH95-12	13	56.5	20.3	13.2	23.5	95	50 / 600
BH120-12	13	64	24.5	15.6	27.7	120	50 / 600
BH150-12	13	69	29	17.4	30.3	150	25 / 300
BH150-16	17	69	29	17.4	30.3	150	25 / 300
BH185-14	15	72	32	19	33.3	185	20 / 240
BH185-16	17	72	32	19	33.3	185	20 / 240
BH240-14	15	92	38	21.8	37.7	240	10 / 120
BH240-16	17	92	38	21.8	37.7	240	10 / 120
BH300-16	17	101	43	24.8	43.9	300	5 / 60
BH400-16	17	110	46	28	49.9	400	5 / 60

